

Turn your printer into a copier with plug-and-play solution

For **instant** project collaboration



Complete with intuitive MFP2GO controller screen

Contex MFP2GO is our easy plug-and-play solution for your large-format printer, when you need to scan, share and copy changes to plans and drawings.

The solution connects easily to your printer, giving you a nice and small footprint, and fits your existing tools and business processes.

You can copy and scan to email, FTP, network, or USB – directly from the simple touch-screen controller.

You get outstanding image quality, with real-time view of enhancements and preset functionality for your daily scanning needs. The Contex MFP2GO bundle includes a scanner, MFP2GO controller, and a high stand.

No additional PC or software needed.



SD 36 MFP2GO



IQ Quattro 24 MFP2GO



IQ Quattro 44 MFP2GO



Low stand version for side-by-side

	IQ Quattro 24 MFP2GO	IQ Quattro 44 MFP2GO	SD 36 MFP2GO
High-stand version¹			
Settings	Right or left side controller mounting. Supported printer height from 995 to 1195 mm in 25 mm increments (39.2 to 47 inches in about 1 inch increments)		
Designed to fit (USB or network)	HP DesignJet T-series, Z-series, and 500/800 series, Canon iPF 600/700/900 series and EPSON SC-T series See full list of supported printers at contex.com/mfp2go		
Low-stand version (Side-by-side)			
Settings	Right or left side controller mounting. Side-by-side. Working height 834 / 859 / 884 mm (32.8 / 33.8 / 34.8 inches)		Right or left side controller mounting. Working Height 821 / 846 / 871 mm (32.3 / 33.3 / 34.3 inches)
Additional printers, side-by-side	EPSON STYLUS PRO, Océ, Mutoh and some HP printers. See full list at www.contex.com/mfp2go		
Scan Destinations			
File formats	Copy / USB / Network / Email / FTP TIF, JPG, PDF, PDF/A, and CALS		
Scanner Specifications (See remaining specifications for the scanner under the product series)			
200 dpi RGB Color speed	2 inch/sec	2 inch/sec	1.5 inch/sec
Upgradable ²	Yes	Yes	Yes
200 dpi Grayscale / Monochrome	14 inch/sec	14 inch/sec	10 inch/sec
Maximum Scan Width	24 inch (610 mm)	44 inch (1118 mm)	36 inch (914 mm)
Maximum Media Width	26.6 inch (676 mm)	47 inch (1194 mm)	38 inch (965 mm)
Optical Resolution	1200 dpi	1200 dpi	600 dpi
Maximum Resolution	9600 dpi	9600 dpi	600 dpi
Technology	Contex CleanScan CIS	Contex CleanScan CIS	Contex Unibody CIS design
Contex SIGMA ³	•	•	•
Contex CFR ⁴	•	•	•
Maximum Media Thickness	0.08 inch (2 mm)	0.08 inch (2 mm)	0.08 inch (2 mm)
Accuracy	0.1% +/- 1 pixel	0.1% +/- 1 pixel	0.1% +/- 1 pixel
Data Capture (color/mono)	48-bit / 16-bit	48-bit / 16-bit	48-bit / 16-bit
Color Space	sRGB	sRGB	sRGB
Energy Star Certified	•	•	•
Power Requirements	100 – 240V, 60/50Hz, 18W	100 – 240V, 60/50Hz, 23W	100 – 240V, 60/50Hz, 25W
Weight	16.1 Kg (35.5 lbs)	27 kg (59.5 lbs)	21.1 kg (46.5 lbs)
Dimensions (LxWxH)	32.4 x 32.4 x 18.9 x 6.3 inches (82.4 x 48.0 x 16.1 cm)	53.1 x 18.9 x 6.3 inches (135.0 x 48.0 x 16.1 cm)	45.6 x 12.9 x 5.5 inches (115.9 x 32.7 x 14 cm)
Certifications/compliance	CE, cUL, Customs Union, Ukr, VCCI, FCC Class A, RoHS, and ENERGY STAR Certified	CE, cUL, Customs Union, Ukr, VCCI, FCC Class A, RoHS, and ENERGY STAR Certified	CE, cUL, Gost-R, Ukr, KC, BSMI, FCC Class A, RoHS, VCCI, ENERGY STAR Certified

MFP2GO Controller specifications

Processor	Intel Cedarview D2550 Dual Core 1.86G, L2 1M, 10W
Memory / Storage	1 GB DDR3 RMA / 160 GB SATA
OS	Windows 7 Embedded
Scanning Software	Build-in scanning and copying software included
Language versions	Chinese, Dutch, English, French, German, Italian, Japanese, Korean, Polish, Russia, Spanish and Portuguese
Touch Screen	10.1" LED LCD, 1024x600 Pixels
Connectivity	USB or Network Printer Support / USB Scanner Support / USB Disk Support / GB Ethernet
Power Supply	65W / 19V
Weight & Dimensions	1.5 kg, WxDxH: 10.4 x 1.5 x 6.7 inches (263 x 38 x 170 mm)
Certifications/compliance	CE, cUL, CCC, KC, PSE, VCCI, FCC Class A, RoHS and ENERGY STAR Certified

1 Not all supported printers will fit under the high stand, but can be used side-by-side.
 2 Upgrading the scanner speed will not be supported by the MFP2GO Controller. For faster scanning speeds the scanner must be connected to a full PC with optional Nextimage Software.
 3 Signal Intensity Matching (SIGMA) is a Contex Patent. Sensor heating during a scan can cause inhomogeneous images. Thanks to Contex innovative thinking, our IQ Quattro and SD scanners will minimize sensor differences LIVE during a scan.

4 Color Fringe Removal (CFR) is a Contex Patent. Color Fringing is a natural consequence of CIS technology sequentially flashing R-G-B. Thanks to Contex innovative thinking CFR will remove this problem with advanced filter technology.
 All trademarks remain the property of their respective holders, and are used only to directly describe the product being provided. Their use in no way indicates any relationship between Contex A/S and the holders of the said trademarks.

User friendly and intuitive touch screen solution – with selected powerful image settings



Easily scan, share and copy directly from plug-and-play controller solution



Preview, crop and adjust image settings directly from controller



Scan-to-copy, -email, -network, -FTP and USB. Import images directly to standard tablets



A good ergonomic environment for left- as well as right-handed operation

Contex Head Office
 Phone: +45 4814 1122
info@contex.com

Contex Americas
 Maryland, USA
 Phone: +1 (703) 964 9850
salesamericas@contex.com

Contex EMEA & AP
 Copenhagen, Denmark
 Phone: +45 4814 1122
emea-ap@contex.com

Contex Singapore
 Phone: +65 6853 8129
apac@contex.com

Contex China
 Shanghai
 Phone: +86 21 6422 2525
info-china@contex.com

Contex Japan
 Tokyo
 Phone: +81 3 3669 5515
info-japan@contex.com



Read more at contex.com



Contex solutions work with all leading large-format printers. For full list, see www.contex.com

