

SIGNOLIT® SI 132 Semi-Matte 170g Economy Greyback Roll-Up Film

Description	<i>Material</i>	- white polypropylene film with grey back
	<i>Coating</i>	- microporous coating
	<i>Properties</i>	- good opacity - good scratch-resistance - reduced reflections on the printed surface - brilliant colour reproduction
	<i>Application</i>	- indoor
	<i>Printing Systems</i>	- bubblejet and piezo
	<i>Inks</i>	- water-based dye and pigmented, latex
Examples of use	<i>Indoor</i>	- posters, POS, roll-up displays, exhibition panels
Laminating	It is necessary to protect the surface if it is subject over a long time to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate. If dye inks are used, SI 132 must be laminated indoor and outdoor to improve light-fastness and smudge-proofness. We recommend to use self-adhesive PP laminating foils for cold lamination.	
Technical data	<i>Base material</i>	white polypropylene film
	<i>Thickness</i>	~ 180 µm
	<i>Grammage</i>	~ 170g/m ²
	<i>Opacity</i>	~ 1,38
	<i>Core</i>	76mm Ø
	<i>Dimensions</i>	914 mm x 50 m 1067 mm x 50 m
Storage	After printing the remaining roll must be removed from the plotter and stored in its closed original packing in a cool and dry environment.	
Disposal	The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.	



Digit Bt.
1125 Budapest, Istenehyi út 29. Phone: +36 1 2245456
Email: info@digit.hu Web: www.nagyformatumu.hu Webshop: www.digitdisplay.eu